LCA | Jerrycans & Buckets

EssentialTech Centre





LEURE

Presentation of items



To store 20 L of liquid for 1 year

1	1	4	
	-	P	-
1	4		3

Foldable Jerrycan 20L

- Lifespan: 3 months
- Mass: 270 grams
- Materials: Mainly virgin
 LDPE



Bucket type OXFAM 14L

- Lifespan: 5 years
- Mass: 860 grams
- Materials: Mainly virgin
- HDPE

ltem		for 20L storage	Reference Flows
Jerrycan	0.25	1.00	4.00
Bucket	5.00	1.43	0.286

Assumptions

Both products manufactured in China with virgin materials, itemps are distributed by sea to the field (Kenya). No use phase considered for jerrycan, bucket washed every year with 5L of water and soap. Open burning in considered as end of life.

Results of the computation



Stage	Store		kgCO₂e			
Stage		Jerrycan	Bucket			
Raw Material		3.41	0.50			
Production		1.91	0.26			
Transportation		0.66	0.09			
Use		0	0.28			
End-of-Life		4.25	0.56			



Stage	Human Health				
Stage	Jerrycan	Bucket			
Raw Material	2.06E-04	2.78E-05			
Production	1.18E-04	1.58E-05			
Transportation	8.11E-05	1.07E-05			
Use	0	2.13E-05			
End-of-Life	8.93E-05	1.18E-05			

Variations (% from baseline figures presented above)



											- 11
Jerrycan	Bucket	Jerrycan	Bucket	Jerrycan	Bucket	Jerrycan	Bucket		Jerrycan	Bucket	
-20.7%	-12.1%	-11.8%	-8.9%	-16.9%	-12.6%	-16.1%	-11.7%		-50.6%	-39.7%	
								U			

Analyses

To shift from buckets to jerrycans for operations can achieve a significant reduction in this field. This product already exists and is used by some organizations, so, it can be operationalized quickly. Then, working with suppliers to manufacture products with recycled materials and renewable energy can further lead to a total reduction of 85% from the baseline jerrycan for the same lifespan. Finally, waste is problematic as few facilities exist for collection and treatment. Severals scenarios had been studied to highlight potential impact reduction, without considering recycling as it is still not an available disposal method in these area of intervention. Advocating for infrastructure development is key to achieving a reduction in end-of-life treatment.

	Name	GHG Protocol Categories	kgCO2e/unit		
(Emission factors)	Name	Gha Protocol Categories	Jerrycans	Buckets	
The sector of the sector and	Cradle-to-grave	N/A	2.03	8.40	
The values displayed here are not per functional unit but per item. These values can be used to compute a carbon footprint of an organisation and can be adapted to a specific case using the tool	Cradle-to-gate	3.1 Purchased Goods	0.83	3.84	
	Distribution freight	3.4 and/or 3.9 Transportation	0.14	0.36	
	Use phase	3.11 Use of distributed product	0	1.40	
	End-of life	3.12 End of life of distributed product	1.06	2.80	

References

Wernet, G., Bauer, C., Steubing, B., Reinhard, J., Moreno-Ruiz, E., and Weidema, B., 2016. '*The ecoinvent database version 3 (part I)*: *overview and methodology*'. The International Journal of Life Cycle Assessment, [online] 21(9), pp.1218–1230. Available at: <u>http://link.springer.com/10.1007/s11367-016-1087-8</u>.

Rajput, A., Tobin Greene, C. and Schmid, S. (no date) 'Life Cycle Assessment (LCA) Methodology'. Available at: <u>https://climateactionaccelerator.org/wp-</u> <u>content/uploads/2025/06/EPFL_LCA_methodology_v1.0.</u> <u>pdf</u>.

Repository of life cycle assessments - Climate Action Accelerator (2025). Available at:

https://climateactionaccelerator.org/repository-oflifecycle-assessments/.

About this project

Designing methodologies and performing life cycle analyses of high-impact items to build a GHG emission factor and environmental impact database adapted to the humanitarian sector with the goal of identifying key strategies to reduce environmental impacts.

EPFL EssentialTech Center: Dr.Grégoire Castella, Dr. Cara Tobin, Emeline Darçot

EPFL LEURE: Dr. Sascha Nick, Ashima Rajput

International Committee of the Red Cross (ICRC): Anna Maria Liwak, Carmen Garcia Duro

Climate Action Accelerator: Bruno Jochum, Sonja Schmid, Paolo Sévègnes

Associated expert: Dr. Damien Friot